



GRAPHIS

The GRAPHIS range offers a smoother plaster-like finish combined with subtle geometric patterns and a unique curved MicroLook edge detail.

Key features

- Very high light reflectance: 92%
- Available in MicroLook edge detail
- High recycled content: 52%

Application areas




















Ideal for reception areas, shops or conference rooms.

OFFICE - BDO Rotterdam (NL)
GRAPHIS Mix A



Inspiring Great Spaces®

Armstrong[®]
CEILING SOLUTIONS

EDGE DETAIL	MICROLOOK																																						
																																							
THICKNESS (mm)	17																																						
MODULES (mm)	600 x 600 ... 9900M 9901M 9220M 9221M 9222M 9223M 9224M																																
SUSPENSION SYSTEMS	Prelude 15 TL / XL ²																																						
PATTERNS	PUNTOS	CUADROS	LINEAR	NEOCUBIC	DIAGONAL	MIX A	MIX B																																
																																							
SUSTAINABILITY	 52   A+  E1																																						
ACOUSTICS	 <p>EN 20140-9 & EN ISO 717-1 EN ISO 354 & EN ISO 11654</p> <table border="1"> <thead> <tr> <th rowspan="2"></th> <th rowspan="2">D_{ncw}</th> <th rowspan="2">α_w</th> <th rowspan="2">Class</th> <th rowspan="2">NRC</th> <th colspan="6">Hz α_p</th> </tr> <tr> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>MicroLook</td> <td>36 dB</td> <td>0.15(L)</td> <td>E</td> <td>0.15</td> <td>0.35</td> <td>0.20</td> <td>0.10</td> <td>0.10</td> <td>0.15</td> <td>0.25</td> </tr> </tbody> </table>												D_{ncw}	α_w	Class	NRC	Hz α_p						125	250	500	1000	2000	4000	MicroLook	36 dB	0.15(L)	E	0.15	0.35	0.20	0.10	0.10	0.15	0.25
	D_{ncw}	α_w	Class	NRC	Hz α_p																																		
					125	250	500	1000	2000	4000																													
MicroLook	36 dB	0.15(L)	E	0.15	0.35	0.20	0.10	0.10	0.15	0.25																													
FIRE REACTION		EEA Euroclass A2-s2, d0 EN 13501-1				RUS KM1 (G1, V1, D1, T1) FZ 123																																	
OTHER PERFORMANCES & FEATURES	 92%	 70% RH		 $\lambda = 0.060$ W/m K EN 12667 & ISO 8301	 6.5 kg/m ²																																		