



ULTIMA+ OP



OFFICE - Swedbank Customer Service Center (LT)
ULTIMA+ OP Tegalur

ULTIMA+ OP not only offers a finely textured and durable surface with a brighter “blue-white” colour for high light reflectance, but is also C2C Bronze certified and provides Class A sound absorption, making it ideal for open plan areas.

Key features

- Excellent sound absorption: 1.00 α_w
- Very high light reflectance: 87%
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee





















Application areas

Ideal for open spaces (call centres, cafeterias...).



Inspiring Great Spaces®

Armstrong®
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90																													
																																
THICKNESS (mm)	20	20	20																													
MODULES (mm)	600 x 600 7682M 625 x 625 7682D 675 x 675 7683M 1200 x 600 7684M	600 x 600 7678M 625 x 625 7678D 675 x 675 7679M 1200 x 600 7680M	600 x 550 7714M 600 x 600 7685M 625 x 625 7685D 675 x 675 7686M 1200 x 600 7687M 1500 x 600 7708M																													
SUSPENSION SYSTEMS	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²																													
COLOURS	 Global White																															
SUSTAINABILITY	   																															
	¹ Depends on thickness, edge detail and size of tile.																															
ACOUSTICS																																
	<table border="1"> <thead> <tr> <th rowspan="2">D_{nfw}</th> <th rowspan="2">R_w</th> <th rowspan="2">α_w</th> <th rowspan="2">Class</th> <th rowspan="2">NRC</th> <th colspan="6">Hz α_p</th> </tr> <tr> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>Board, Tegular, MicroLook 90</td> <td>25 dB</td> <td>10 dB</td> <td>1.00</td> <td>A</td> <td>0.95</td> <td>0.40</td> <td>0.80</td> <td>1.00</td> <td>0.95</td> <td>1.00</td> <td>1.00</td> </tr> </tbody> </table>			D _{nfw}	R _w	α _w	Class	NRC	Hz α _p						125	250	500	1000	2000	4000	Board, Tegular, MicroLook 90	25 dB	10 dB	1.00	A	0.95	0.40	0.80	1.00	0.95	1.00	1.00
D _{nfw}	R _w	α _w	Class						NRC	Hz α _p																						
				125	250	500	1000	2000		4000																						
Board, Tegular, MicroLook 90	25 dB	10 dB	1.00	A	0.95	0.40	0.80	1.00	0.95	1.00	1.00																					
FIRE REACTION		EEA Euroclass A2-s1, d0 EN 13501-1	RUS KM1 (G1, V1, D1, T1) FZ 123																													
OTHER PERFORMANCES & FEATURES	 87%  λ = 0.037 W/m K EN 12667 & ISO 8301	 95% RH  3.2 kg/m ²	 ISO 5 ISO 14644-1  	 30YEAR system guarantee  BIM READY																												
CUSTOM OPTIONS	 Dimensions																															