



## PARAFON HYGIEN (ISO 4)

PARAFON HYGIEN offers a winning balance of Class A sound absorption, washability and hygiene performances.

### Key features

- Suitable for high pressure water cleaning (max 80 bars)\*
- Excellent sound absorption: 0.95  $\alpha_w$
- ISO 4

### Application areas

Ideal for kitchen and healthcare areas.




















HEALTHCARE - Kitchen  
PARAFON HYGIEN



Inspiring Great Spaces®

**Armstrong**<sup>®</sup>  
CEILING SOLUTIONS

# PARAFON HYGIEN (ISO 4)

<b>EDGE DETAIL</b>	<b>BOARD</b>										
											
<b>THICKNESS (mm)</b>	<b>18</b>										
<b>MODULES (mm)</b>	600 x 600 . . . . . 9702M 625 x 625 . . . . . 9702D 1200 x 600 . . . . . 9703M										
<b>SUSPENSION SYSTEMS</b>	Prelude 24 XL <sup>2</sup> / TL <sup>2</sup> Prelude 24 Corrosive Resistant Clean Room 24										
<b>COLOURS</b>	 Global White										
<b>SUSTAINABILITY</b>	 20				 A		 E1				
<b>ACOUSTICS</b>	 EN ISO 354 & EN ISO 11654										
	<b>Hz <math>\alpha_p</math></b>										
	<b><math>\alpha_w</math></b>	<b>Class</b>	<b>NRC</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>4000</b>		
Board	<b>0.95</b>	A	0.95	0.40	0.85	0.90	0.90	0.95	0.90		
<b>FIRE REACTION</b>	 EEA Euroclass A2-s1, d0 EN 13501-1										
<b>OTHER PERFORMANCES &amp; FEATURES</b>	 82%		 95% RH		 ISO 4 ISO 14644-1		 <sup>1</sup>		 30YEAR system guarantee		 BIM READY
	 $\lambda = 0.033 \text{ W/m K}$ EN 12667 & ISO 8301		 1.3 kg/m <sup>2</sup>								
<b>CUSTOM OPTIONS</b>	 Dimensions										
	<sup>1</sup> The application must be in the form of a fan spray of min 30° angle and not a high pressure “cutting” jet. The suggested minimum distance between the nozzle and the ceiling tile should not be less than 300 mm and the angle of projection should be 45°. PARAFON HYGIEN should be installed with Armstrong Prelude 24 Corrosive Resistant grid and be clipped for high pressure water cleaning. Cleaning recommended twice a year.										