



## CLEAN ROOM FL (ISO 5)

CLEAN ROOM FL features a special polyester film facing providing excellent ISO clean room performance making it an ideal solution for clean room and computer environments, especially in combination with Armstrong CLEAN ROOM 24 grid system.

### Key features

- ISO 5
- Does not attract dust
- Adapted to regular washing

### Application areas

Ideal for computer rooms and clean room environments.
















HEALTHCARE  
CLEAN ROOM FL



Inspiring Great Spaces®

**Armstrong**<sup>®</sup>  
CEILING SOLUTIONS

# CLEAN ROOM FL (ISO 5)

<b>EDGE DETAIL</b>	<b>BOARD</b>											
												
<b>THICKNESS (mm)</b>	<b>15</b>											
<b>MODULES (mm)</b>	600 x 600 ..... 9527M 1200 x 600 ..... 9529M											
<b>SUSPENSION SYSTEMS</b>	Prelude 24 XL <sup>2</sup> / TL <sup>2</sup> Prelude 24 Corrosive Resistant Clean Room 24											
<b>COLOURS</b>	 Global White											
<b>SUSTAINABILITY</b>	 39   A+  E1											
<b>ACOUSTICS</b>	 EN 20140-9 & EN ISO 717-1    EN ISO 354 & EN ISO 11654											
					<b>Hz <math>\alpha_p</math></b>							
		<b>D<sub>ncw</sub></b>	<b><math>\alpha_w</math></b>	<b>Class</b>	<b>NRC</b>	125	250	500	1000	2000	4000	
Board		<b>36 dB</b>	<b>0.15</b>	E	0.10	0.25	0.15	0.10	0.10	0.15	0.25	
<b>FIRE REACTION</b>		EEA Euroclass A2-s1, d0 EN 13501-1				RUS KM1 (G1, V1, D1, T1) FZ 123						
<b>OTHER PERFORMANCES &amp; FEATURES</b>	 78%  95% RH  ISO 5 ISO 14644-1  $\lambda = 0.06 \text{ W/m K}$ EN 12667 & ISO 8301  5.3 kg/m <sup>2</sup>  30 YEAR system guarantee  BIM READY											