



# NEEVA

The smooth laminated finish of the NEEVA products combines Class A sound absorption and aesthetics.

## Key features

- Excellent sound absorption: up to 1.00  $\alpha_w$
- Painted edges to improve the mechanical strength
- Fibre glass fleece on the back to add strength

## Application areas
























Ideal for open spaces (call centres, libraries, cafeteria...).

OFFICE - Dutch Technology (NL)  
NEEVA Board 1200 x 1200 mm



Inspiring Great Spaces®

**Armstrong**<sup>®</sup>  
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR 90	MICROLOOK 90								
											
THICKNESS (mm)	15/18	18	18								
MODULES (mm)	600 x 600 x 15 ..... 2691M 1200 x 600 x 15 ..... 2692M 600 x 600 x 18 ..... 2404M 625 x 625 x 18 ..... 2404D 675 x 675 x 18 ..... 2409M 1200 x 600 x 18 ..... 2405M 1200 x 1200 x 18 ..... 2406M 1250 x 625 x 18 ..... 2405D 1800 x 300 x 18 ..... 2408M 1800 x 600 x 18 ..... 2407M 1350 x 600 x 18 ..... 2410M 1350 x 675 x 18 ..... 2411M	600 x 600 ..... 2414M 675 x 675 ..... 2418M 1200 x 600 ..... 2415M 1200 x 1200 ..... 2416M	600 x 600 ..... 2423M 675 x 675 ..... 2427M 1200 x 600 ..... 2424M								
SUSPENSION SYSTEMS	Prelude 24 XL <sup>2</sup> / TL <sup>2</sup> Prelude 24 CR / TL <sup>2</sup> Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TL <sup>2</sup>	Prelude 24 XL <sup>2</sup> / TL <sup>2</sup> Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TL <sup>2</sup>	Prelude 15 TL / XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette 6mm XL <sup>2</sup>								
COLOURS	COLORTONE NEEVA										
	 Global White	 Black (BK)	 Cement (CG)	 Navy (NY)	 Metal (MT)						
SUSTAINABILITY	 20		 A	 E1							
ACOUSTICS				<b>Hz α<sub>p</sub></b>							
	<b>D<sub>ncw</sub></b>	<b>R<sub>w</sub></b>	<b>α<sub>w</sub></b>	<b>Class</b>	<b>NRC</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>4000</b>
• Board (15 mm)	-	<b>7 dB</b>	<b>1.00</b>	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00
• Board (18 mm)	<b>24 dB</b>	-	<b>1.00</b>	A	0.95	0.40	0.85	1.00	0.90	1.00	0.95
• Tegular 90, MicroLook 90	<b>27 dB</b>	-	<b>0.90</b>	A	0.85	0.40	0.75	0.85	0.85	0.95	0.95
FIRE REACTION		EEA Euroclass A1 EN 13501-1				RUS KM1 (G1, V1, D1, T1) FZ 123					
OTHER PERFORMANCES & FEATURES	 82%	 95% RH									
	 λ = 0.033 W/m K EN 12667 & ISO 8301	 1.2 kg/m <sup>2</sup> Board (15 mm) 1.3 kg/m <sup>2</sup> Board (18 mm) 2.5 kg/m <sup>2</sup> Tegular 90 & MicroLook 90 (18 mm)									
CUSTOM OPTIONS	 Dimensions										