



COLORTONE RANGE

COLORTONE offers a simple way to play with colours in ceilings, available in DUNE eVo or NEEVA surfaces to suit your acoustic requirements.

Key features

- 3 edge details available (DUNE eVo)
- Excellent acoustical absorption:
1.00 α_w (NEEVA)

Application areas

Ideal for cafeterias, cinemas, theatres.






















LEISURE - Uttoxeter Cinema (UK)
COLORTONE NEEVA Black



Inspiring Great Spaces®

Armstrong[®]
CEILING SOLUTIONS

COLORTONE DUNE eVo

EDGE DETAIL	BOARD	TEGULAR 90	MICROLOOK 90																												
THICKNESS (mm)	15	15	15																												
MODULES (mm)	600 x 600 5460MCA 1200 x 600 5461MCA 600 x 600 5460MPN 1200 x 600 5461MPN 600 x 600 5460MBT 1200 x 600 5461MBT	600 x 600 5462MCA 600 x 600 5462MPN 600 x 600 5462MBT	600 x 600 5464MCA 600 x 600 5464MPN 600 x 600 5464MBT																												
SUSPENSION SYSTEMS	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²																												
COLOURS	 Carrara (CA)  Platinum (PN)  Blue Mountain (BT)																														
SUSTAINABILITY	 44   A  E1																														
ACOUSTICS	  <table border="1"> <thead> <tr> <th rowspan="2">Board, Tegular, MicroLook</th> <th rowspan="2">D_{nfw}</th> <th rowspan="2">α_w</th> <th rowspan="2">Class</th> <th rowspan="2">NRC</th> <th colspan="6">Hz α_p</th> </tr> <tr> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td></td> <td>34 dB</td> <td>0.60</td> <td>C</td> <td>0.50</td> <td>0.40</td> <td>0.40</td> <td>0.60</td> <td>0.55</td> <td>0.55</td> <td>0.50</td> </tr> </tbody> </table>			Board, Tegular, MicroLook	D _{nfw}	α _w	Class	NRC	Hz α _p						125	250	500	1000	2000	4000		34 dB	0.60	C	0.50	0.40	0.40	0.60	0.55	0.55	0.50
Board, Tegular, MicroLook	D _{nfw}	α _w	Class						NRC	Hz α _p																					
				125	250	500	1000	2000		4000																					
	34 dB	0.60	C	0.50	0.40	0.40	0.60	0.55	0.55	0.50																					
FIRE REACTION	 EEA Euroclass A2-s1, d0 <small>EN 13501-1</small>		RUS KM1 (G1, V1, D1, T1) <small>FZ 123</small>																												
OTHER PERFORMANCES & FEATURES	 Up to 72%  95% RH  λ = 0.060 W/m K <small>EN 12667 & ISO 8301</small>  ≈ 3.6 kg/m ²     30YEAR system guarantee  BIM READY																														
CUSTOM OPTIONS	 Colours ¹  Dimensions																														

¹ Prelude suspension systems are available in following standard colours: Black (BK), Silver Grey RAL9006 (SG), Brass (BS), Chrome (CE), White RAL9010 (WR). A choice of over 180 RAL colours is available as a special order.