



ULTIMA+



OFFICE – Woningbouwvereniging Compagn (NL)
ULTIMA+ Vector

ULTIMA+ not only offers a finely textured and durable surface with a brighter “blue-white” colour and high light reflectance, it also offers a balance of both sound absorption and sound attenuation as well as being C2C Bronze certified.

Key features

- Good sound absorption: up to 0.75 (H) α_w
- Very high light reflectance: 87%
- Reinforced scratch resistant face
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee
- Available with SL2 MicroLook 90 edge detail

Application areas

Ideal for meeting rooms or waiting areas
ULTIMA+ Planks: ideal for both open areas and corridors.



Inspiring Great Spaces®

Armstrong[®]
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	VECTOR	FINESSE	SL2	K2C2					
THICKNESS (mm)	19	19	19	19	19	19	19					
MODULES (mm)	600 x 600 7661M 625 x 625 7661D 675 x 675 7662M 1200 x 600 7663M 1250 x 625 7663D	600 x 600 7664M 625 x 625 7664D 675 x 675 7665M 1200 x 600 7666M	500 x 500 7673M 600 x 550 7713M 600 x 600 7674M 625 x 625 7674D 675 x 675 7675M 1200 x 300 7676M 1200 x 600 7677M 1500 x 600 7703M	600 x 600 7681M 625 x 625 7681D	600 x 600 7715M 1200 x 600 7716M	1500 x 300 7699M 1720 x 300 7700M 1800 x 300 7701M 2500 x 300 7702M	1500 x 312.5 7667D 1800 x 312.5 7668D 2500 x 312.5 7669D					
SUSPENSION SYSTEMS	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	System Z - L-Bar	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar	System Z - T-Bar System Z - Z-Bar					
COLOURS	 Global White											
SUSTAINABILITY						¹ Depends on thickness, edge detail and size of tile. ² Except Vector: A						
ACOUSTICS	 EN ISO 10848-2 & EN ISO 717-1 EN ISO 140-3 & EN ISO 717-1 EN ISO 354 & EN ISO 11654											
				Hz α_p								
		D_{nfw}	R_w	α_w	Class	NRC	125	250	500	1000	2000	4000
• Board, Tegular, MicroLook 90		36 dB	18 dB	0.70(H)	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00
• Vector		33 dB	-	0.75(H)	C	0.75	0.35	0.55	0.65	0.80	0.95	0.90
• Finesse		39 dB	-	0.70(H)	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00
• SL2 / K2C2		40 dB	-	0.65(H)	C	0.65	0.35	0.45	0.55	0.75	0.90	1.00
FIRE REACTION		EEA Euroclass A2-s1, d0 EN 13501-1				RUS KM1 (G1, V1, D1, T1) FZ 123						
OTHER PERFORMANCES & FEATURES	87% λ = 0.052 W/m K EN 12667 & ISO 8301	95% RH 5.0 kg/m ² (Board, Tegular, MicroLook 90, Finesse) 5.6 kg/m ² (SL2 / K2C2) 5.8 kg/m ² (Vector)	ISO 5 ISO 14644-1 	 	30YEAR system guarantee BIM READY							
CUSTOM OPTIONS	 Dimensions											