



SAHARA

OFFICE - Laurus/SuperdeBoer (NL)
SAHARA MicroLook

The popular SAHARA lightly textured and microperforated surface combines good sound absorption and sound attenuation performance. It is available in a range of sizes including the unique Vector edge detail.

Key features

- High sag resistance
- Good acoustical absorption and sound reduction
- Available in a wide range of sizes and edge details

Application areas

Ideal for school environments, classrooms, offices...



EDGE DETAIL	BOARD	TEGULAR	MICROLOOK	MICROLOOK BE	VECTOR	SL2	K2C2					
THICKNESS (mm)	15 / 17	15	15	15	19	17	17					
MODULES (mm)	Perforated 600 x 600 x 15... 2516M 625 x 625 x 15... 2516D 675 x 675 x 15... 2520M 1200 x 600 x 15... 2517M 1250 x 625 x 15... 2517D 1720 x 300 x 17... 2728M 1500 x 300 x 17... 2315M 1800 x 300 x 17... 2316M 2500 x 300 x 17... 2317M Unperforated 600 x 600 x 15... 2610M	Perforated 600 x 600... 2518M 625 x 625... 2518D 675 x 675... 2521M 1200 x 600... 2522M Unperforated 600 x 600... 2612M	Perforated 600 x 600... 2519M 625 x 625... 2519D 1200 x 600... 2731M Unperforated 600 x 600... 2613M	Perforated 600 x 600... 2524M 675 x 675... 2690M	Perforated 600 x 600... 3322M	Perforated 1500 x 300... 2310M 1720 x 300... 2311M 1800 x 300... 2312M 2500 x 300... 2318M	Perforated 1500 x 312.5... 2313D 2500 x 312.5... 2548D					
SUSPENSION SYSTEMS	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	Prelude 15 TL / XL ² Interlude HRC XL ²	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²	Prelude 24 XL ² / TL ² Prelude 24 Sixty ² XL ² / TL ²	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar	System Z - T-Bar System Z - Z-Bar					
COLOURS & PATTERNS		Option: 		COLORTONE DUNE eVo 								
SUSTAINABILITY												
		31-35 ¹		A+ / A / B	E1		¹ Depends on thickness, edge detail and size of tile.					
ACOUSTICS												
		EN ISO 10848-2 & EN ISO 717-1	EN ISO 140-3 & EN ISO 717-1	EN ISO 354 & EN ISO 11654								
		D_{nfw}	R_w	α_w	Class	NRC	125	250	500	1000	2000	4000
	PERFORATED											
	• Board, Tegular, MicroLook, MicroLook BE	34 dB	17 dB	0.60	C	0.55	0.45	0.40	0.55	0.65	0.65	0.60
	• Vector	35 dB	-	0.65	C	0.65	0.45	0.50	0.60	0.70	0.70	0.55
	• SL2/K2C2	39 dB	-	0.60	C	0.55	0.55	0.35	0.45	0.60	0.55	0.45
	UNPERFORATED											
	• Board, Tegular, MicroLook	34 dB	-	0.10(L)	E	0.15	0.30	0.20	0.10	0.10	0.10	0.20
FIRE REACTION		EEA Euroclass A2-s1, d0 EN 13501-1				RUS KM1 (G1, V1, D1, T1) FZ 123						
OTHER PERFORMANCES & FEATURES	85% (unperforated) 84% (perforated)	95% RH										
	λ = 0.060 W/m K EN 12667 & ISO 8301	≈ 3.5 - 3.9 kg/m ² Board, Tegular, MicroLook, MicroLook BE (15mm) 5.5 kg/m ² SL2, Board (17mm) 6.0 kg/m ² Vector										
CUSTOM OPTIONS												
	Dimensions											